

# SPLIT RING SELECTION GUIDE

No.5196 P-12



SPLIT RING  
HYPER WIRE



No.4180 P-25



SPLIT RING  
ULTRA WIRE




No.72843 P-43



CAST RING  
SHIELD WIRE



## STRENGTH



SINGLE	#3	#4	#5	#6	#7	#8	#9	#10
<b>P-12</b>	46	50	61	70	83	115	156	190
<b>P-25</b>	75	90	110	150	215	240	320	370
<b>P-43</b>				99	112	144	167	206

\*All measurements represented in (lb)

DOUBLE	#3	#4	#5	#6	#7	#8	#9	#10
<b>P-12</b>	76	77	101	119	163	235	240	339
<b>P-25</b>	125	150	185	250	365	405	540	625
<b>P-43</b>				167	173	277	299	372

\*All measurements represented in (lb)

## WEIGHT

	#3	#4	#5	#6	#7	#8	#9	#10
<b>P-12</b>	0.16	0.17	0.24	0.30	0.42	0.67	0.97	1.36
<b>P-25</b>	0.24	0.32	0.41	0.60	0.77	1.12	1.57	2.35
<b>P-43</b>				0.47	0.63	0.94	1.36	1.84

\*All measurements represented in (g)

## WHAT IS THE DIFFERENCE?

**P-12**




**Ideal for "Jigging"**

- Easy and quick lure changing
- Finish : **STAINLESS**

P-12	#3	#4	#5	#6	#7	#8	#9	#10
<b>ID</b>	4.5	5.0	5.5	6.0	7.0	8.0	9.0	10.0
<b>OD</b>	6.3	6.8	7.5	8.2	9.4	10.8	12.2	13.6
<b>WD</b>	0.9	0.9	1.0	1.1	1.2	1.4	1.6	1.8

\*All measurements represented in (mm)



**P-25**



**Ideal for "Big Target"**

- Ideal for anglers who give importance to "strength"
- **Light but strong**
- Keep closed while repeatedly lure changing
- Finish : **STAINLESS**

P-25	#3	#4	#5	#6	#7	#8	#9	#10
<b>ID</b>	4.5	5.0	5.5	6.0	7.0	8.0	9.0	10.0
<b>OD</b>	6.7	7.4	8.1	9.0	10.2	11.6	13.0	14.6
<b>WD</b>	1.1	1.2	1.3	1.5	1.6	1.8	2.0	2.3

\*All measurements represented in (mm)

**P-43**



**Ideal for "Lure Casting"**

- Designed with moderate balance between weight and strength
- Combine the best of both worlds; Balanced weight and strength for **enhancing lure presentation**
- Finish : **ZINC**

P-43	#3	#4	#5	#6	#7	#8	#9	#10
<b>ID</b>				6.0	7.0	8.0	9.0	10.0
<b>OD</b>				8.6	9.8	11.2	12.6	14.0
<b>WD</b>				1.3	1.4	1.6	1.8	2.0

\*All measurements represented in (mm)